



## CONFIGURATION

<b>L</b>	Control	Standard Screw Adjustment
<b>A</b>	Reverse Flow Check	4 psi (0,3 bar)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b> Material/Coating		

Needle valves with reverse-flow check are fully adjustable orifices used to regulate flow. They are infinitely adjustable from fully closed up to the maximum orifice diameter. An integral high-capacity check valve provides unrestricted flow from port 2 to port 1. They are not pressure compensated.

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990016007
Seal kit - Cartridge	Polyurethane: 990016002
Seal kit - Cartridge	Viton: 990016006

## CONFIGURATION OPTIONS

Model Code Example: NCFCCLAN

CONTROL	(L) REVERSE FLOW CHECK	(A) SEAL MATERIAL	(N) MATERIAL/COATING
<b>L</b> Standard Screw Adjustment	<b>A</b> 4 psi (0,3 bar)	<b>N</b> Buna-N	Standard Material/Coating
<b>H</b> Calibrated Handknob with Detent Lock	<b>C</b> 30 psi (2 bar)	<b>E</b> EPDM	/AP Stainless Steel, Passivated
<b>K</b> Handknob	<b>E</b> 75 psi (5 bar)	<b>V</b> Viton	/LH Mild Steel, Zinc-Nickel
<b>Y</b> Tri-Grip Handknob			