



CONFIGURATION

X	Control	No Manual Override
C	Spool Configuration	Normally Closed
N	Seal Material	Buna-N
(none)	Coil	No coil

This solenoid-operated 2-way, 2-position cartridge is a direct-acting, balanced spool directional valve. The valve is available in either a normally open or normally closed configuration and is designed to be used with 740 and 747 Series coils.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	80 cc/min.@210 bar
Manual Override Force Requirement	33 N/100 bar @ Port 1
Manual Override Stroke	2,5 mm
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
Seal kit - Cartridge	Buna: 990413007
Seal kit - Cartridge	Viton: 990413006

NOTES

Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.

CONFIGURATION OPTIONS

Model Code Example: DLDFXCN

CONTROL	(X) SPOOL CONFIGURATION	(C) SEAL MATERIAL	(N) COIL *
X No Manual Override	C Normally Closed	N Buna-N	No coil
D Twist/Lock (Dual) Manual Override	H Normally Open	E EPDM	* Additional coil options are available
L Twist/Lock (Detent) Manual Override		V Viton	
M Manual Override			
T Twist (Momentary) Manual Override			