



**CONFIGURATION**

<b>X</b>	Control	Not Adjustable
<b>C</b>	Setting Range	30 psi (2 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b> Material/Coating		

This valve is a fixed-orifice, non-pressure-compensated flow control with a reverse flow check. The flow setting is specified by the user and is set at the factory.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 3,9 mm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

**CONFIGURATION OPTIONS**

Model Code Example: **CNCCXCN**

<b>CONTROL</b>	<b>(X) SETTING RANGE</b>	<b>(C) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
<b>X</b> Not Adjustable	<b>C</b> 30 psi (2 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)	<b>N</b> Buna-N <b>V</b> Viton	Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel
	<b>A</b> 4 psi (0,3 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)		
	<b>B</b> 15 psi (1 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)		
	<b>D</b> 50 psi (3,5 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)		
	<b>E</b> 75 psi (5 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)		
	<b>F</b> 100 psi (7 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)		