



CONFIGURATION

H Minimum Pilot Pressure	200 psi (14 bar)
N Seal Material	Buna-N

This is a normally open, balanced poppet, switching element with an integral T-8A control cavity. With a 2-way valve in the closed position installed in the T-8A control cavity, the poppet remains open. Opening the 2-way valve shifts the poppet to the closed position, provided there is sufficient pressure at port 3.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Minimum Pilot Pressure Required to Shift Valve	20 bar
Control Pilot Flow	See Performance Data
Maximum Valve Leakage at 110 SUS (24 cSt)	0,7 cc/min.@350 bar
Pilot Control Cavity	T-8A
Pilot Control Valve Installation Torque	27 - 33 Nm
Pilot Control Valve Hex Size	22,2 mm
Seal kit - Cartridge	Buna: 990023007
Seal kit - Cartridge	Polyurethane: 990023002
Seal kit - Cartridge	Viton: 990023006

CONFIGURATION OPTIONS

Model Code Example: DOHR8HN

MINIMUM PILOT PRESSURE	(H)	SEAL MATERIAL	(N)
H 200 psi (14 bar)		N Buna-N	
		V Viton	