

M-Control, C-Poppet


This FLeX Series, solenoid-operated 2-way, 2-position cartridge is a direct-acting directional poppet valve. Available in either normally open or normally closed configurations, these valves feature a pressure-balanced design, low leakage, and allow flow or blocking in both directions.

CONFIGURATION

M	Control	Manual Override
C	Poppet Configuration	Normally Closed
N	Seal Material	Buna-N
(none)	Coil	No coil

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.@350 bar
Viscosity Range	2,8 - 380 cSt
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
U.S. Patent #	10,302,201
Seal kit - Cartridge	Buna: 990162007
Seal kit - Cartridge	Viton: 990162006

NOTES

- Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.
- An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.

CONFIGURATION OPTIONS

Model Code Example: DTBFMCN

CONTROL	(M) POPPET CONFIGURATION	(C) SEAL MATERIAL	(N) COIL *
M Manual Override	C Normally Closed	N Buna-N	No coil
D Twist/Lock (Dual) Manual Override	H Normally Open	E EPDM	* Additional coil options are available
L Twist/Lock (Detent) Manual Override		V Viton	
T Twist (Momentary) Manual Override			
X No Manual Override			