



**CONFIGURATION**

<b>X</b> Control	Standard Pilot, Atmospheric Vent
<b>C</b> Cracking Pressure	30 psi (2 bar)
<b>N</b> Seal Material	Buna-N

This valve is a pilot to open check valve. It has a sealed pilot, a steel seat, and is vented. It allows free flow from the valve (port 2) to the load (port 1) and blocks flow in the opposite direction. Pressure at the pilot (port 3) pilot port will open the valve from port 1 to port 2. Pilot pressure needed to open the valve is directly proportional to the load pressure at port 1. The valve is insensitive to pressure at port 2 because the spring chamber is referenced out the back of the hex body.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Locknut Hex Size	11,1 mm
Seal kit - Cartridge	Buna: 990202007
Seal kit - Cartridge	Polyurethane: 990002002
Seal kit - Cartridge	Viton: 990202006

**CONFIGURATION OPTIONS**

Model Code Example: **CKEVXCN**

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)
<b>X</b> Standard Pilot, Atmospheric Vent		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N	
<b>S</b> External 4-SAE Vent Port		<b>A</b> 4 psi (0,3 bar)		<b>V</b> Viton	
		<b>B</b> 15 psi (1 bar)			
		<b>D</b> 50 psi (3,5 bar)			
		<b>E</b> 75 psi (5 bar)			
		<b>F</b> 100 psi (7 bar)			