



CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
N	Seal Material	Buna-N
(none) Material/Coating		

Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990162007
Seal kit - Cartridge	EPDM: 990162014
Seal kit - Cartridge	Polyurethane: 990162002
Seal kit - Cartridge	Viton: 990162006

CONFIGURATION OPTIONS

Model Code Example: **CXBAXAN**

CONTROL	(X) CRACKING PRESSURE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A 4 psi (0,3 bar)	N Buna-N	Standard Material/Coating
	C 30 psi (2 bar)	E EPDM	/AP Stainless Steel, Passivated
	B 15 psi (1 bar)	V Viton	/LH Mild Steel, Zinc-Nickel
	D 50 psi (3,5 bar)		
	E 75 psi (5 bar)		
	F 100 psi (7 bar)		