


CONFIGURATION

X	Control	Not Adjustable
F	Cracking Pressure	100 psi (7 bar)
N	Seal Material	Buna-N
(none) Material/Coating		



Free-flow, side-to-nose check valves are on/off circuit components that allow free flow from the inlet (port 2) to the outlet (port 1) and block flow in the opposite direction.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990016007
Seal kit - Cartridge	EPDM: 990016014
Seal kit - Cartridge	Polyurethane: 990016002
Seal kit - Cartridge	Viton: 990016006

CONFIGURATION OPTIONS

Model Code Example: **CXGD**XFN

CONTROL	(X)	CRACKING PRESSURE	(F)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		F 100 psi (7 bar)		N Buna-N		Standard Material/Coating
		C 30 psi (2 bar)		E EPDM		/AP Stainless Steel, Passivated
		A 4 psi (0,3 bar)		V Viton		/LH Mild Steel, Zinc-Nickel
		B 15 psi (1 bar)				
		D 50 psi (3,5 bar)				
		E 75 psi (5 bar)				