





CONFIGURATION

/S Modifier 65-45-12 Ductile Iron, Buna-N,
Dewatering Oil

TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Through port with gauge port
Mounting Hole Thread	M6x1.0 - 6H
Mounting Hole Depth	12,7 mm
Mounting Hole Quantity	2

NOTES *Important:* Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
FEV, /10, /11, /S, /S3	Ports 1 & 2: 1/2" BSPP; Gage Ports: 1/4" BSPP;

CONFIGURATION OPTIONS

Model Code Example: FEV/S

MODIFIER	(/S)
/S	65-45-12 Ductile Iron, Buna-N, Dewatering Oil
	6061-T651 Aluminum, Buna-N
/10	6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
/11	6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
/S3	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
/S4	65-45-12 Ductile Iron, Buna-N, Chem. Black
/S5	65-45-12 Ductile Iron, Buna-N, Electroless Nickel