


CONFIGURATION

/S Modifier 65-45-12 Ductile Iron, Buna-N,
Dewatering Oil



TECHNICAL DATA

Body Type	Line mount
Interface	None
Body Features	Ninety degree
Mounting Hole Diameter	10,7 mm
Mounting Hole Depth	Through
Mounting Hole Quantity	2

NOTES *Important:* Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

PORT DESIGNATORS

Modifiers	Ports
HCM, /10, /11, /S, /S3, /S4, /S5	Ports 1 & 2: SAE 16; Port 3: SAE 6;

CONFIGURATION OPTIONS

Model Code Example: HCMArray

MODIFIER (S)

- /S 65-45-12 Ductile Iron, Buna-N, Dewatering Oil
- 6061-T651 Aluminum, Buna-N
- /10 6061-T651 Aluminum, Buna-N, Black
Anodize - Per MIL SPEC 8625F Type II, Class II
- /11 6061-T651 Aluminum, Buna-N, Clear
Anodize - Per MIL SPEC 8625F Type II, Class I
- /S3 65-45-12 Ductile Iron, Buna-N, Trivalent
Clear Zinc with Top Sealer
- /S4 65-45-12 Ductile Iron, Buna-N, Chem. Black
- /S5 65-45-12 Ductile Iron, Buna-N, Electroless

Nickel