



**CONFIGURATION**

<b>X</b>	Control	Standard Pilot
<b>C</b>	Cracking Pressure	30 psi (2 bar)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	

This valve is a pilot to open check valve. It has a sealed pilot, a steel seat, and is vented. It allows free flow from the valve (port 2) to the load (port 1) and blocks flow in the opposite direction. Pressure at the pilot (port 3) will open the valve from port 1 to port 2. Pilot pressure needed to open the valve is directly proportional to the load pressure at port 1. The valve is insensitive to pressure at port 2 because the spring chamber is referenced to the vent (port 4).

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Pilot Volume Displacement	4,9 cc
Pilot Passage into Valve	2,3 mm
Locknut Hex Size	11,1 mm
Seal kit - Cartridge	Buna: 990024007
Seal kit - Cartridge	EPDM: 990024014
Seal kit - Cartridge	Polyurethane: 990024002
Seal kit - Cartridge	Viton: 990024006

**CONFIGURATION OPTIONS**

**Model Code Example: CVIVXCN**

<b>CONTROL</b>	<b>(X)</b>	<b>CRACKING PRESSURE</b>	<b>(C)</b>	<b>SEAL MATERIAL</b>	<b>(N)</b>	<b>MATERIAL/COATING</b>
<b>X</b> Standard Pilot		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N		Standard Material/Coating
<b>L</b> Manual Load Release		<b>A</b> 4 psi (0,3 bar)		<b>V</b> Viton		/AP Stainless Steel, Passivated
		<b>B</b> 15 psi (1 bar)				/LH Mild Steel, Zinc-Nickel
		<b>D</b> 50 psi (3,5 bar)				
		<b>E</b> 75 psi (5 bar)				
		<b>F</b> 100 psi (7 bar)				