


CONFIGURATION

X	Control	Not Adjustable
A	Setting Range	Replaceable Orifice 1 - 15 gpm (4 - 60 L/min.)
N	Seal Material	Buna-N
(none)	Material/Coating	

Flow fuse cartridges are used to maintain the position of a hydraulic actuator in the event of a hose or line break. The valve allows flow to and from the actuator but closes instantly if flow from the actuator exceeds the setting of the valve. NOTE: Because the valve responds so rapidly, it is sensitive to any transient flow above the valve setting.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	50 cc/min.@70 bar
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	Viton: 990203006

CONFIGURATION OPTIONS
Model Code Example: FQEAXAN

CONTROL	(X) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	A Replaceable Orifice 1 - 15 gpm (4 - 60 L/min.)	N Buna-N V Viton	Standard Material/Coating /AP Stainless Steel, Passivated