



**CONFIGURATION**

<b>D</b>	Control	External 1/8 BSPP Port
<b>C</b>	Spool Configuration	Normally Closed
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	

These pilot-stage, directional, 2-position, 2-way valves are hydraulically operated, spring-return cartridges and are available in either a normally open or normally closed configuration. These cartridges are designed for pilot flow applications and utilize Sun's T-8A cavity so they can be used in conjunction with Sun's pilot-operated, main-stage valves.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Minimum Pilot Pressure to Operate	See Technical Features
Pilot Control Port	See Control Options
Seal kit - Cartridge	Buna: 990508007
Seal kit - Cartridge	Viton: 990508006

**CONFIGURATION OPTIONS**

Model Code Example: DAAHDCN

<b>CONTROL</b>	<b>(D) SPOOL CONFIGURATION</b>	<b>(C) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
<b>D</b> External 1/8 BSPP Port	<b>C</b> Normally Closed	<b>N</b> Buna-N	Standard Material/Coating
<b>A</b> External 1/8 NPTF Port	<b>H</b> Normally Open	<b>V</b> Viton	/AP Stainless Steel, Passivated
<b>B</b> External 4-SAE Port			