



CONFIGURATION

X	Control	Not Adjustable, Standard Hydraulic Pilot
C	Bias Pressure	30 psi (2 bar)
V	Seal Material	Viton
(none) Material/Coating		

This valve is a pilot to open check valve. It has a sealed pilot, a steel seat, and is non-vented. It allows free flow from the valve (port 2) to the load (port 1) and blocks flow in the opposite direction. Pressure at the pilot (port 3) will open the valve from port 1 to port 2. Pilot pressure needed at port 3 to open the valve is directly proportional to the load pressure at port 1. Pressure at port 2 directly opposes pilot pressure.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Internal Hex Size	8 mm
Seal kit - Cartridge	Buna: 990163007
Seal kit - Cartridge	Polyurethane: 990163002
Seal kit - Cartridge	Viton: 990163006

CONFIGURATION OPTIONS

Model Code Example: **CKBGXCV**

CONTROL	(X)	BIAS PRESSURE	(C)	SEAL MATERIAL	(V)	MATERIAL/COATING
X Not Adjustable, Standard Hydraulic Pilot		C 30 psi (2 bar) E 75 psi (5 bar)		V Viton N Buna-N		Standard Material/Coating /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel