


**CONFIGURATION**

<b>E</b>	Control	External 4-SAE Port
<b>X</b>	Adjustment Range	-
<b>N</b>	Seal Material	Buna-N
<b>(none)</b> Material/Coating		

The single ball shuttle connects the higher of two work ports to the signal or common port. The signal is sensed at an external port located in the hex-end of the cartridge.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

**CONFIGURATION OPTIONS**
**Model Code Example: CSAAEXN**

<b>CONTROL</b>	<b>(E) ADJUSTMENT RANGE</b>	<b>(X) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
<b>E</b> External 4-SAE Port	<b>X</b> -	<b>N</b> Buna-N	Standard Material/Coating
<b>B</b> External 1/4 BSPP Port		<b>E</b> EPDM	/AP Stainless Steel, Passivated
		<b>V</b> Viton	/LH Mild Steel, Zinc-Nickel