



CONFIGURATION

L	Control	Standard Screw Adjustment
G	Maximum Orifice Diameter	.56 in. (14,2 mm)
N	Seal Material	Buna-N
(none) Material/Coating		

Needle valves are fully adjustable orifices used to regulate flow. They are infinitely adjustable from fully closed up to the maximum orifice diameter. They are not pressure compensated and may be used as flow controls or as shutoff valves.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990018007
Seal kit - Cartridge	EPDM: 990018014
Seal kit - Cartridge	Polyurethane: 990018002
Seal kit - Cartridge	Viton: 990018006

CONFIGURATION OPTIONS

Model Code Example: NFFCLGN

CONTROL	(L)	MAXIMUM ORIFICE DIAMETER	(G)	SEAL MATERIAL	(N)	MATERIAL/COATING
L Standard Screw Adjustment		G .56 in. (14,2 mm)		N Buna-N		Standard Material/Coating
H Calibrated Handknob with Detent Lock		H .38 in. (9,7 mm)		E EPDM		/AP Stainless Steel, Passivated
K Handknob				V Viton		/LH Mild Steel, Zinc-Nickel
Y Tri-Grip Handknob, Flow Control						