



CONFIGURATION

X	Control	Not Adjustable
C	Setting Range	30 psi (2 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)
N	Seal Material	Buna-N
(none)	Material/Coating	

Free-flow, side-to-nose cheater check valves with a bypass orifice function as a 2-port check valve in a 3-port cavity. They allow free flow from port 2 to port 1 with a customer specified orifice that controls flow from port 1 to port 2. Port 3 of the cartridge is blocked off.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 3,4 mm
Seal kit - Cartridge	Buna: 990202007
Seal kit - Cartridge	Polyurethane: 990002002
Seal kit - Cartridge	Viton: 990202006

CONFIGURATION OPTIONS

Model Code Example: **CNEDXCN**

CONTROL	(X) SETTING RANGE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable	C 30 psi (2 bar) Cracking Pressure, .016 - .135 in. (0,4 - 3,4 mm)	N Buna-N V Viton	Standard Material/Coating /LH Mild Steel, Zinc-Nickel