



CONFIGURATION

L	Control	Standard Screw Adjustment
C	Adjustment Range	.1 - 1 gpm (0,4 - 4 L/min.)
N	Seal Material	Buna-N
(none)	Material/Coating	

Fully adjustable, pressure-compensated flow controls with reverse-flow check provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. They are infinitely adjustable from nearly closed up to the maximum flow. An integral high-capacity check valve provides unrestricted flow from port 2 to port 1.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Adjustment - No. of CCW Turns from Fully Closed to Fully Open	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	EPDM: 990010014
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

NOTES For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.

CONFIGURATION OPTIONS

Model Code Example: FDBALCN

CONTROL	(L) ADJUSTMENT RANGE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	C .1 - 1 gpm (0,4 - 4 L/min.)	N Buna-N	Standard Material/Coating
H Calibrated Handknob with Detent Lock	A .1 - 6 gpm (0,4 - 23 L/min.)	E EPDM	/AP Stainless Steel, Passivated
K Handknob	B .1 - 2 gpm (0,4 - 8 L/min.)	V Viton	/LH Mild Steel, Zinc-Nickel
Y Tri-Grip Handknob			