



CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
V	Seal Material	Viton
(none) Material/Coating		

Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	EPDM: 990010014
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

CONFIGURATION OPTIONS

Model Code Example: CXDAXAV

CONTROL	(X)	CRACKING PRESSURE	(A)	SEAL MATERIAL	(V)	MATERIAL/COATING
X Not Adjustable		A 4 psi (0,3 bar)		V Viton		Standard Material/Coating
		C 30 psi (2 bar)		N Buna-N		/AP Stainless Steel, Passivated
		B 15 psi (1 bar)		E EPDM		/LH Mild Steel, Zinc-Nickel
		D 50 psi (3,5 bar)				
		E 75 psi (5 bar)				
		F 100 psi (7 bar)				