



CONFIGURATION

K	Control	Handknob
A	Setting Range	Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)
N	Seal Material	Buna-N
(none) Material/Coating		

Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	EPDM: 990203014
Seal kit - Cartridge	Viton: 990203006

CONFIGURATION OPTIONS

Model Code Example: FXDAKAN

CONTROL	(K) SETTING RANGE	(A) SEAL MATERIAL	(N) MATERIAL/COATING
K Handknob	A Replaceable Orifice .1 - 12 gpm (0,4 - 45 L/min.)	N Buna-N	Standard Material/Coating
L Tuning Adjustment		E EPDM	/AP Stainless Steel, Passivated
X Not Adjustable		V Viton	/LH Mild Steel, Zinc-Nickel
C Tamper Resistant - Factory Set			