


sunhydraulics.com/model/RDHA

CONFIGURATION

L	Control	Standard Screw Adjustment
B	Adjustment Range	300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) Standard Setting
N	Seal Material	Buna-N
(none) Material/Coating		

Direct-acting relief cartridges are normally closed, pressure-limiting valves used to protect hydraulic components from pressure transients. When the pressure at the inlet (port 1) reaches the valve setting, the valve starts to open to tank (port 2), throttling flow to limit the pressure rise. These valves are smooth and quiet, essentially zero leak, dirt tolerant, immune to silting and are very fast.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	15 L/min.
Maximum Valve Leakage at Reseat	0,7 cc/min.
Response Time - Typical	2 ms
Reseat	>90% of setting
Adjustment - No. of CW Turns from Min. to Max. setting	6
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990316007
Seal kit - Cartridge	Viton: 990316006

NOTES U.S. Patent #4,742,846; European Patent Pending

CONFIGURATION OPTIONS

Model Code Example: RDHAArray

CONTROL	(L) ADJUSTMENT RANGE	(B) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	B 300 - 1500 psi (20 - 105 bar), 1000 psi (70 bar) Standard Setting A 500 - 3000 psi (35 - 210 bar), 1000 psi (70 bar) Standard Setting W 800 - 4500 psi (55 - 315 bar), 1000 psi (70 bar) Standard Setting C 1000 - 6000 psi (70 - 420 bar), 1000 psi (70 bar) Standard Setting D 200 - 800 psi (14 - 55 bar), 400 psi (28 bar) Standard Setting E 100 - 400 psi (7 - 28 bar), 200 psi (14 bar) Standard Setting S 50 - 200 psi (3,5 - 14 bar), 100	N Buna-N	Standard Material/Coating
C Tamper Resistant - Factory Set		E EPDM	/AP Stainless Steel, Passivated
		V Viton	/LH Mild Steel, Zinc-Nickel

psi (7 bar) Standard Setting