



### CONFIGURATION

<b>X</b>	Control	Not Adjustable
<b>F</b>	Flow Rate	60 in <sup>3</sup> /min. (1 L/min.)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b> Material/Coating		

Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. A variety of flow rates are available.

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Seal kit - Cartridge	Buna: 990008007
Seal kit - Cartridge	EPDM: 990008014
Seal kit - Cartridge	Polyurethane: 990008002
Seal kit - Cartridge	Viton: 990008006

### CONFIGURATION OPTIONS

Model Code Example: FXAAXFN

CONTROL	(X) FLOW RATE	(F) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>F</b> 60 in <sup>3</sup> /min. (1 L/min.)	<b>N</b> Buna-N	Standard Material/Coating
	A 15 in <sup>3</sup> /min. (250 cc/min.)	E EPDM	/AP Stainless Steel, Passivated
	B 20 in <sup>3</sup> /min. (330 cc/min.)	V Viton	/LH Mild Steel, Zinc-Nickel
	D 40 in <sup>3</sup> /min. (660 cc/min.)		
	H 80 in <sup>3</sup> /min. (1.3 L/min.)		
	J 100 in <sup>3</sup> /min. (1.6 L/min.)		
	L 120 in <sup>3</sup> /min. (2.0 L/min.)		