



CONFIGURATION

X	Control	Standard Pilot
C	Cracking Pressure	30 psi (2 bar)
N	Seal Material	Buna-N
(none)	Material/Coating	

This valve is a spring biased closed, pilot-to-close check cartridge that has a 3:1 pilot ratio. The valve allows flow from port 1 to port 2 and blocks reverse flow. Pressure at the pilot port opposes pressure at port 1 at a ratio of 3:1. This valve is most often used in regeneration circuits.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990163007
Seal kit - Cartridge	EPDM: 990163014
Seal kit - Cartridge	Polyurethane: 990163002
Seal kit - Cartridge	Viton: 990163006

CONFIGURATION OPTIONS

Model Code Example: **COBAXCN**

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Standard Pilot		C 30 psi (2 bar)		N Buna-N		Standard Material/Coating
B External 1/4 BSPP Pilot Port, Port 3 blocked		D 50 psi (3,5 bar)		E EPDM		/AP Stainless Steel, Passivated
		E 75 psi (5 bar)		V Viton		/LH Mild Steel, Zinc-Nickel
		F 100 psi (7 bar)				