


**CONFIGURATION**

<b>X</b>	Control	Not Adjustable
<b>C</b>	Cracking Pressure	30 psi (2 bar)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b> Material/Coating		



Free-flow, side-to-nose check valves are on/off circuit components that allow free flow from the inlet (port 2) to the outlet (port 1) and block flow in the opposite direction.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990203007
Seal kit - Cartridge	Viton: 990203006

**CONFIGURATION OPTIONS**

**Model Code Example: CXEDXCN**

<b>CONTROL</b>	<b>(X)</b>	<b>CRACKING PRESSURE</b>	<b>(C)</b>	<b>SEAL MATERIAL</b>	<b>(N)</b>	<b>MATERIAL/COATING</b>
<b>X</b> Not Adjustable		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N		Standard Material/Coating
		<b>A</b> 4 psi (0,3 bar)		<b>E</b> EPDM		/AP Stainless Steel, Passivated
		<b>B</b> 15 psi (1 bar)		<b>V</b> Viton		/LH Mild Steel, Zinc-Nickel
		<b>D</b> 50 psi (3,5 bar)				
		<b>E</b> 75 psi (5 bar)				
		<b>F</b> 100 psi (7 bar)				