



Pilot-operated, pressure reducing/relieving valves reduce a high primary pressure at the inlet (port 2) to a constant reduced pressure at port 1, with a full-flow relief function from port 1 to tank (port 3).

### CONFIGURATION

<b>K</b>	Control	Handknob
<b>N</b>	Adjustment Range	75 - 800 psi (5 - 55 bar), 200 psi (14 bar) Standard Setting
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Factory Pressure Settings Established at	blocked control port (dead headed)
Control Pilot Flow	0,11 - 0,16 L/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	12,7 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990163007
Seal kit - Cartridge	EPDM: 990163014
Seal kit - Cartridge	Polyurethane: 990163002
Seal kit - Cartridge	Viton: 990163006

**NOTES** Maximum pressure differentials for spring ranges: A and B are 3000 psi (210 bar) N and Q are 2000 psi (140 bar) W is 5000 psi (350 bar) inlet pressure

### CONFIGURATION OPTIONS

Model Code Example: PPBBArray

CONTROL	(K) ADJUSTMENT RANGE	(N) SEAL MATERIAL	(N) MATERIAL/COATING
<b>K</b> Handknob	<b>N</b> 75 - 800 psi (5 - 55 bar), 200 psi (14 bar) Standard Setting	<b>N</b> Buna-N	Standard Material/Coating
<b>L</b> Standard Screw Adjustment		<b>E</b> EPDM	/AP Stainless Steel, Passivated
<b>C</b> Tamper Resistant - Factory Set	<b>A</b> 75 - 3000 psi (5 - 210 bar), 200 psi (14 bar) Standard Setting	<b>V</b> Viton	/LH Mild Steel, Zinc-Nickel
	<b>B</b> 75 - 1500 psi (5 - 105 bar), 200 psi (14 bar) Standard Setting		
	<b>Q</b> 75 - 400 psi (5 - 28 bar), 200 psi (14 bar) Standard Setting		
	<b>W</b> 100 - 4500 psi (7 - 315 bar), 200 psi (14 bar) Standard Setting		