


**CONFIGURATION**

|                                |                   |                 |
|--------------------------------|-------------------|-----------------|
| <b>X</b>                       | Control           | Not Adjustable  |
| <b>A</b>                       | Cracking Pressure | 4 psi (0,3 bar) |
| <b>N</b>                       | Seal Material     | Buna-N          |
| <b>(none)</b> Material/Coating |                   |                 |

Free-flow, side-to-nose check valves are on/off circuit components that allow free flow from the inlet (port 2) to the outlet (port 1) and block flow in the opposite direction.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|   |                  |
|---|------------------|
| Maximum Operating Pressure                | 350 bar          |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,07 cc/min.     |
| Seal kit - Cartridge                      | Buna: 990203007  |
| Seal kit - Cartridge                      | Viton: 990203006 |

**CONFIGURATION OPTIONS**
**Model Code Example: CXEDXAN**

| <b>CONTROL</b>          | <b>(X)</b> | <b>CRACKING PRESSURE</b>  | <b>(A)</b> | <b>SEAL MATERIAL</b> | <b>(N)</b> | <b>MATERIAL/COATING</b>         |
|-------------------------|------------|---------------------------|------------|----------------------|------------|---------------------------------|
| <b>X</b> Not Adjustable |            | <b>A</b> 4 psi (0,3 bar)  |            | <b>N</b> Buna-N      |            | Standard Material/Coating       |
|                         |            | <b>C</b> 30 psi (2 bar)   |            | <b>E</b> EPDM        |            | /AP Stainless Steel, Passivated |
|                         |            | <b>B</b> 15 psi (1 bar)   |            | <b>V</b> Viton       |            | /LH Mild Steel, Zinc-Nickel     |
|                         |            | <b>D</b> 50 psi (3,5 bar) |            |                      |            |                                 |
|                         |            | <b>E</b> 75 psi (5 bar)   |            |                      |            |                                 |
|                         |            | <b>F</b> 100 psi (7 bar)  |            |                      |            |                                 |