



**CONFIGURATION**

<b>X</b>	Control	Not Adjustable
<b>F</b>	Differential Pressure	100 psi (7 bar)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b>	Material/Coating	

Normally open modulating elements without an internal orifice act as a restrictive compensator to maintain a constant pressure drop across an orifice, regardless of variations in upstream or downstream pressure.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006

**CONFIGURATION OPTIONS**

Model Code Example: LPDCXFN

CONTROL	(X) DIFFERENTIAL PRESSURE	(F) SEAL MATERIAL	(N) MATERIAL/COATING
<b>X</b> Not Adjustable	<b>F</b> 100 psi (7 bar) D 50 psi (3,5 bar) G 150 psi (10,5 bar) H 200 psi (14 bar)	<b>N</b> Buna-N E EPDM V Viton	<b>Standard Material/Coating</b> /AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel