



CONFIGURATION

L	Control	Standard Screw Adjustment
S	Adjustment Range	25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting
N	Seal Material	Buna-N
(none) Material/Coating		

Direct-acting, 3-way directional cartridges (3 to 4 open, 2 blocked) are switching devices typically used in moderate flow circuits. They can be used by themselves or to actuate larger pilot operated directional cartridges or logic cartridges. The valve shifts when the pressure differential between port 1 and port 4 exceeds the setting.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	30 cc/min.
Adjustment - No. of CW Turns from Min. to Max. setting	5
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990021007
Seal kit - Cartridge	Polyurethane: 990021002
Seal kit - Cartridge	Viton: 990021006

CONFIGURATION OPTIONS

Model Code Example: DRBRLSN

CONTROL	(L) ADJUSTMENT RANGE	(S) SEAL MATERIAL	(N) MATERIAL/COATING
L Standard Screw Adjustment	S 25 - 200 psi (1,7 - 14 bar), 100 psi (7 bar) Standard Setting	N Buna-N	Standard Material/Coating
C Tamper Resistant - Factory Set	E 25 - 400 psi (1,7 - 28 bar), 200 psi (14 bar) Standard Setting	V Viton	/AP Stainless Steel, Passivated
K Handknob	N 60 - 800 psi (4 - 55 bar), 200 psi (14 bar) Standard Setting		/LH Mild Steel, Zinc-Nickel
O Handknob with Panel Mount			