


X-Control, C-Poppet



CONFIGURATION

X	Control	No Manual Override
C	Poppet Configuration	Normally Closed
N	Seal Material	Buna-N
(none)	Coil	No coil

This FLeX Series solenoid-operated 2-way, 2-position cartridge is a direct-acting directional poppet valve. Available in either normally open or normally closed configurations, these valves feature a pressure-balanced design, low leakage, and allow flow or blocking in both directions.

This cartridge can be installed directly into a cavity in the end of many of Sun's pilot operated and ventable valves to provide integrated pilot control.

TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.@350 bar
Viscosity Range	2,8 - 380 cSt
Response Time - Typical	50 ms
Switching Frequency	15,000 max. cycles/hr
U.S. Patent #	10,302,201
Seal kit - Cartridge	Buna: 990608007
Seal kit - Cartridge	Viton: 990608006

NOTES

- For Series 1 cartridges configured with an O control (panel mount handknob), a .75 in. (19 mm) diameter hole is required in the panel.
- Please verify cartridge clearance requirements when choosing a Sun manifold. Different valve controls and coils require different clearances.
- An additional 2.00 inches (50,8 mm) beyond the valve extension is needed for coil installation and removal.

CONFIGURATION OPTIONS

Model Code Example: DTAFXCN

CONTROL	(X)	POPPET CONFIGURATION	(C)	SEAL MATERIAL	(N)	COIL *
X No Manual Override		C Normally Closed		N Buna-N		No coil
D Twist/Lock (Dual) Manual Override		H Normally Open		E EPDM		* Additional coil options are available
L Twist/Lock (Detent) Manual Override				V Viton		
M Manual Override						
T Twist (Momentary) Manual Override						