



**CONFIGURATION**

<b>X</b>	Control	Standard Pilot
<b>D</b>	Cracking Pressure	50 psi (3,5 bar)
<b>V</b>	Seal Material	Viton
<b>(none)</b>	Material/Coating	

This valve is a spring biased closed, pilot-to-close check cartridge that has a 20:1 pilot ratio. The valve allows flow from port 1 to port 2 and blocks reverse flow. Pressure at the pilot (port 3) opposes pressure at port 1 at a ratio of 20:1.

**TECHNICAL DATA**

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990011007
Seal kit - Cartridge	EPDM: 990011014
Seal kit - Cartridge	Polyurethane: 990011002
Seal kit - Cartridge	Viton: 990011006

**CONFIGURATION OPTIONS**

Model Code Example: **CODDXDV**

CONTROL	(X) CRACKING PRESSURE	(D) SEAL MATERIAL	(V) MATERIAL/COATING
<b>X</b> Standard Pilot	<b>D</b> 50 psi (3,5 bar) <b>H</b> 200 psi (14 bar)	<b>V</b> Viton <b>E</b> EPDM <b>N</b> Buna-N	<b>Standard Material/Coating</b> <b>/AP</b> Stainless Steel, Passivated