



### CONFIGURATION

<b>L</b>	Control	Tuning Adjustment
<b>A</b>	Setting Range	Replaceable Orifice .1 - 6 gpm (0,4 - 23 L/min.)
<b>N</b>	Seal Material	Buna-N
<b>(none)</b> Material/Coating		

Fixed-orifice, pressure-compensated flow controls provide precise flow regulation for meter-in or meter-out applications where there may be wide pressure fluctuations. The flow setting is specified by the user and is set at the factory.

### TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Locknut Hex Size	15 mm
Locknut Torque	9 - 10 Nm
Seal kit - Cartridge	Buna: 990010007
Seal kit - Cartridge	EPDM: 990010014
Seal kit - Cartridge	Polyurethane: 990010002
Seal kit - Cartridge	Viton: 990010006

### CONFIGURATION OPTIONS

**Model Code Example: FXCALAN**

<b>CONTROL</b>	<b>(L) SETTING RANGE</b>	<b>(A) SEAL MATERIAL</b>	<b>(N) MATERIAL/COATING</b>
<b>L</b> Tuning Adjustment	<b>A</b> Replaceable Orifice .1 - 6 gpm (0,4 - 23 L/min.)	<b>N</b> Buna-N	Standard Material/Coating
<b>X</b> Not Adjustable		<b>E</b> EPDM	/AP Stainless Steel, Passivated
<b>K</b> Handknob		<b>V</b> Viton	/LH Mild Steel, Zinc-Nickel